Spirolab New[™]

MIR Quick Guide


For more detailed information on any section in this guide please refer to the included user manual. (Located on CD)

С

Overview



- Micro USB-to-PC connection
- Thermal Printer paper container
- Wall charger connection
- Miniflowmeter connection
- (optional) Oximeter connection



В

Α

G

F.

MIR USA, Inc.

G

1900 Pewaukee Road, Suite D - Waukesha, WI 53188 **P** +1 (262) 565 - 6797 **F** +1 (262) 364 - 2030 mirusa@spirometry.com www.spirometry.com

MIR ITALY, Head Office

AN MIR

Via del Maggiolino, 125 - 00155 Roma **P** +39 06 22 754 777 **F** +39 06 22 754 785 mir@spirometry.com www.spirometry.com

Setting up your device





Connect the Miniflowmeter with the black arrow on connector plug facing up.



TURNING THE SPIROLAB ON

To turn the Spirolab on, press then release the button on the front of the unit. The display will automatically display the main screen after a few seconds.



BATTERY CHARGE

The internal battery pack charge is shown in the upper right hand corner of the display by the symbol. If the battery symbol is all green then the battery is fully charged.

TURNING THE SPIROLAB OFF

To turn the Spirolab off press and hold the power button until the unit shuts down (approximately 5 seconds).

MIR USA, Inc.

 1900 Pewaukee Road, Suite D - Waukesha, WI 53188

 P +1 (262) 565 - 6797
 F +1 (262) 364 - 2030

 mirusa@spirometry.com
 www.spirometry.com

MIR ITALY, Head Office

 Via del Maggiolino, 125 - 00155 Roma

 P +39 06 22 754 777
 F +39 06 22 754 785

 mir@spirometry.com
 www.spirometry.com





(A) Thermal paper

To remove the thermal paper before it is empty:




remove the printer cover.

- Then lift the release lever located, if you are looking at the back of the device, to the left of the printer.
- Once that is done go ahead and remove the thermal paper roll.
- Then lower the release lever back into place.



The device's features can be accessed from the main screen. The last patient tested will by default be the one that comes up on the main screen, even when the device has been turned on/off.





MIR USA, Inc.

 1900 Pewaukee Road, Suite D - Waukesha, WI 53188

 P +1 (262) 565 - 6797
 F +1 (262) 364 - 2030

 mirusa@spirometry.com
 www.spirometry.com

MIR ITALY, Head Office

 Via del Maggiolino, 125 - 00155 Roma

 P +39 06 22 754 777
 F +39 06 22 754 785

 mir@spirometry.com
 F www.spirometry.com



Symbols and icons

SETTINGS	To access initial settings (service menu)		To check the alarms and thresholds set during an oximetry test
ADD/SEL	To enter new patient data		To check the oximetry sensor is properly connected during testing
MODIFY	To edit patient data/To rerun an archived patient test	E	To check the presence of a signal during the oximetry test
ARCHIVE	To access file containing tests performed	PRINT	To print a test A screen with 3 choices will pop open:
¢	To save the settings and return to the main screen	INTERNAL	- print to the internal thermal printer
	To view the last originate version	UNDO	- to cancel the print operation
	To view the last spirometry session for the current patient		- to print to an external USB connected printer
DATA	To view the last oximetry session for the current patient		lcons that show up when loading the thermal paper into the thermal printer:
OXY	To test oximetry	PAPER	- press to manually feed more through the printer if necessary
FVC	To test FVC spirometry	ОК	- touch OK when finished with paper install
vc	To test VC spirometry	UNDO	To cancel an operation and return to the previous step
	To test MVV spirometry		To delete a test
POST	To run a bronchodilator test (POST)	EXIT	To exit without saving

MIR USA, Inc.

MIR ITALY, Head Office




Spirolab Settings

The Spirolab New comes already configured. However if you need to change any of the configuration follow the steps below.

- 1
- To get into settings touch the **settings icon** and enter the password **122333**.

On the left highlighted in orange is the subject, then on the top highlighted in orange is a corresponding topic.

Selecting different subjects and tabs shows you the different settings that can be changed. (for more details check the user manual)



Main settings screen

Entering patient data




On the main screen click on the add/sel patient icon.

The next screen you see allows you touch type in all the patient information, you can touch the **OK icon** to go to the next field or touch inside the next field's box.



When you are finished, the **save/exit** icon must be selected. This will save the information and take you back to the main screen.



Patient data screen

MIR USA, Inc.

 1900 Pewaukee Road, Suite
 - Waukesha, WI 53188

 P +1 (262) 565 - 6797
 F +1 (262) 364 - 2030


 mirusa@spirometry.com
 www.spirometry.com

MIR ITALY, Head Office

Via del Maggiolino, 125 - 00155 Roma **P** +39 06 22 754 777 **F** +39 06 22 754 785 mir@spirometry.com www.spirometry.com

AN MIR

Testing



=

PRINT

Printing



Select the **print icon** while on the results screen, the data screen, or even the main screen.



Choose internal icon to print on the thermal printer.



NOTE: If you print from the main screen it will print out the last test results for that patient. If an oximetry spot check was just done that is the test it will print out.

NOTE: If connected up via USB cable (NOT INCLUDED) to a compatible printer. (Compatible printer list is being updated). Refer to the user manual for more information on this feature.

MIR USA. Inc.

1900 Pewaukee Road, Suite D - Waukesha, WI 53188 **P** +1 (262) 565 - 6797 **F** +1 (262) 364 - 2030 mirusa@spirometry.com www.spirometry.com

MIR ITALY. Head Office

Via del Maggiolino, 125 - 00155 Roma **P** +39 06 22 754 777 **F** +39 06 22 754 785 mir@spirometry.com www.spirometry.com

MIR

Archive



Select the **archive icon** to search the archive for:

- viewing previous test data on a specific patient;
- selecting and retesting a patient already entered into the Spirolab New;
- printing previous test data.
- On the Archive screen there are 10 parameters that you can search by. Touch the box to the right of the parameter to make it turn orange and that parameter is now part of the search parameters.




Choose the **OK icon** to continue to the search results.

When the information for the search is found the search results screen will let select the patient data you are specifically looking for.

Then select the patient so that it is highlighted in orange.

- Now select an option from the icons on the bottom of the screen. A test icon to retest the patient or a data icon to view the data.
 - When viewing the data, if you want to retest the patient choose a test icon.
- A verification screen will come up if you choose to retest that patient.
- Choose **Undo** to return to the search results or **OK** to continue to the testing screen.

Now that patient will be the one that shows up on the main screen, even when turning the device on/off.



Archive screen



Search results screen

MIR USA, Inc.

 1900 Pewaukee Road, Suite
 D - Waukesha, WI 53188

 P +1 (262) 565 - 6797
 F +1 (262) 364 - 2030

 mirusa@spirometry.com
 www.spirometry.com

MIR ITALY, Head Office

 Via del Maggiolino, 125 - 00155 Roma

 P +39 06 22 754 777
 F +39 06 22 754 785

 mir@spirometry.com
 www.spirometry.com